



PRODUCT-DETAILS

1VCF337111R1362
VD4 12.12.40 P210



General Information

Product ID:	1VCF337111R1362
Catalog Description:	VD4 12.12.40 P210
Display Name:	1VCF337111R1362

Certificates and Declarations

Data Sheet, Technical Information:	1VCP000001_A
Instructions and Manuals:	647654

Dimensions

Product Net Weight:	75 kg
---------------------	-------

Additional Information

Rated Voltage (U _r):	12 kV
----------------------------------	-------

Rated Impulse Withstand Voltage (U _{imp}):	75 kV
Power Frequency Withstand Voltage:	28 kV
Rated Frequency (f):	50/60 Hz
Rated Current (I _n):	1250 A
Rated Short-time Withstand Current Low Voltage (I _{cw}):	for 3 s 40 kA
Rated Short-Circuit Capacity:	40 kA DC Component 35 %
Rated Short-Circuit Making Capacity (I _{cm}):	100 kA
Rated Cable-Charging Breaking Current:	25 A
Operating Sequence:	O-0,3S-CO-15S-CO
Suitable for Product Class:	E2,M2,C2
Ambient Temperature:	-5 ... 40 °C
Product Main Type:	VD4
Product Name:	VD4 12.12.40 P210
Distance Between Phases:	210 mm

Categories

Products > Medium Voltage Products and Systems > Circuit Breakers > Indoor Vacuum Circuit Breakers

